



Tucson

PRODUCT SPECIFICATIONS

| | |
|--------------------|--------------------------------------|
| Style | R3032 |
| Construction | Multicolor Level Cut Loop |
| Fiber | 100% Solution-dyed Primus® PET Fiber |
| Twist Level | 4.91 TPI |
| Gauge | 1/10 |
| Tufted Pile Weight | 26 oz. / sq. yd. |
| Pile Height | 0.312" Cut / 0.250" Loop |
| Stitches Per Inch | 9 |
| Primary Backing | Woven Polypropylene |
| Secondary Backing | Actionbac® |
| Dye | Solution-dyed |
| Total Weight | 62 oz. |
| Density | 3000 |
| Width | 12' |
| Pattern Repeat | 12"W x 15"L |

Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad. **Stretch-In Installation:** Establish roll sequencing, dry lay carpet, and apply latex seam sealer to both edges. Pre-stretch the sections with shorter pattern measurements to align with longer patterns in order to make hot melt seam (**use 6" tape to prevent seam peaking**). A two-headed power stretcher or "deadman" must be used to achieve this. Once the seam is made, proceed with proper stretch installation (CRI-104, figure "Stretch Diagram"). The use of architectural or double tackless strip is required to be used throughout a stretch-in installation.

Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. **IT IS NOT A CARPET DEFECT**, but is inherent in solution-dyed graphic and cut/loop patterns.

All specifications subject to normal manufacturing tolerance.

Tarkett North America

285 Kraft Drive
Dalton, GA 30721
USA: 800-871-3211

www.tarkettna.com

©Tarkett USA Inc. 10/2019