



Westchester

PRODUCT SPECIFICATIONS

Style	R3060
Construction	Multicolor Level Cut Loop
Fiber	100% Solution-dyed Primus® PET Fiber
Twist Level	4.91 TPI
Gauge	1/10
Tufted Pile Weight	34 oz. / sq. yd.
Pile Height	0.375" Cut / 0.343" Loop
Stitches Per Inch	10
Primary Backing	Woven Polypropylene
Secondary Backing	Actionbac®
Dye	Solution-dyed
Total Weight	70 oz.
Density	3264
Width	12'
Pattern Repeat	12"W x 12"L

Carpet should be installed in accordance with the Carpet and Rug Institute's standard CRI-104. Carpet must be over manufacturer's recommended pad. **Stretch-In Installation:** Establish roll sequencing, dry lay carpet, and apply latex seam sealer to both edges. Pre-stretch the sections with shorter pattern measurements to align with longer patterns in order to make hot melt seam (**use 6" tape to prevent seam peaking**). A two-headed power stretcher or "deadman" must be used to achieve this. Once the seam is made, proceed with proper stretch installation (CRI-104, figure "Stretch Diagram"). The use of architectural or double tackless strip is required to be used throughout a stretch-in installation.

Pattern streaks and banding are visually apparent streaking in patterned carpet resulting from linear juxtaposition of pattern elements visible in both length and width direction. **IT IS NOT A CARPET DEFECT**, but is inherent in solution-dyed graphic and cut/loop patterns.

All specifications subject to normal manufacturing tolerance.

Tarkett North America

285 Kraft Drive
Dalton, GA 30721
USA: 800-871-3211

www.tarkettna.com

©Tarkett USA Inc. 10/2019