

**1. PROPRIETARY PRODUCT/MANUFACTURER**

1.1 **Proprietary Product:** Fiberglass-reinforced luxury resilient sheet vinyl that can be heat welded. Suitable for Residential and Light Commercial environments. Features Techtonic™ Technology protective coating for increased durability; resisting scratching, abrasions and staining to keep the floor looking better and lasting longer.

**1.2 Manufacturer:**

Tarkett North America Phone: (800) 899-8916  
30000 Aurora Rd. (440) 543-8916  
Solon, Ohio 44139  
Web: [www.tarketthome.com](http://www.tarketthome.com)

**1.3 Proprietary Product Description:**

1.3.1 **Construction:** Luxury resilient sheet vinyl made from ortho-phthalate free, virgin raw materials with Techtonic polyurethane coating technology.

**1.3.2 Characteristics:**

- **Construction:** Urethane Topcoat (Low Gloss) Techtonic Technology
- **Series:** 60000
- **Overall Thickness:** 0.080" (2.03 mm)
- **Wearlayer Thickness:** 0.020" (0.51 mm)
- **Width:** 12' (3.6 m)
- **Maximum Roll Size:** 100 yd<sup>2</sup> (83.6 m<sup>2</sup>)
- **Weight per Square Yard:** 4.81 lbs. (2.18 kg)

**2. PRODUCT DETAILS AND TECHNICAL DATA**

- 2.1 **Sheet Material:** ASTM F1303 Type 1, Grade 1, Class C
- 2.2 **Slip Resistance:** ASTM D2047 >0.5
- 2.3 **Flexibility:** ASTM F137 Passes
- 2.4 **Static Load Limit:** ASTM F970 175 lbs./in<sup>2</sup> (12.3 kg/cm<sup>2</sup>)
- 2.5 **Heat Stability:** ASTM F1514 ΔE<8
- 2.6 **Light Stability:** ASTM F1515 ΔE<8
- 2.7 **Sound Reduction:** ASTM E2179 ΔIIC 13 dB
- 2.8 **Stain Resistance:** ASTM F925 Passes
- 2.9 **Fire Performance:** ASTM E648 >0.45 W/cm<sup>2</sup>
- 2.10 **Smoke Density:** ASTM E662 <450
- 2.11 **HUD/FHA Minimum Property Standards:** Meets Wearlayer Thickness
- 2.12 **FloorScore® Certification:** SCS-FS-02746
- 2.13 **Asthma and Allergy Certified:** AAFC: 1155/11/05/01/2066

**Tarkett North America**

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
888-639-8275

[Resilient.TechnicalSupport@tarkett.com](mailto:Resilient.TechnicalSupport@tarkett.com)

[www.tarketthome.com](http://www.tarketthome.com)

**3. INSTALLATION**

See FiberFloor installation instructions found at [www.tarketthome.com](http://www.tarketthome.com) for complete details.

**3.1 Methods:**

- Releasable
- Permanent
- Floating Glueless

**3.2 Adhesive:**

- **Tarkett Qbond One or Tarkett SwiftGrip**  
Releasable - Medium Nap Roller  
Permanent - 1/32" x 1/16" x 1/32" trowel

**3.3 Seaming:**

- **Seam Sealer:** Tarkett DT-65 (Low Gloss)
- **Heat Welding**

**4. AVAILABILITY AND COST**

Available through Tarkett Distributors and Retailers.

**5. MAINTENANCE**

See Residential Maintenance instructions found at [www.tarketthome.com](http://www.tarketthome.com) for complete details.

**6. TECHNICAL SERVICES**

Visit us on the web at [www.tarketthome.com](http://www.tarketthome.com)

Contact Technical Support at (888) 639 8275, or E-mail [Resilient.TechnicalSupport@tarkett.com](mailto:Resilient.TechnicalSupport@tarkett.com)

**7. WARRANTY**

- LIFETIME LIMITED RESIDENTIAL WARRANTY  
Aquaguard® 2 year "No Questions Asked" Warranty
- 15 YEAR LIGHT COMMERCIAL WARRANTY



**ORTHO-PHTHALATE  
FREE**