## 1. PROPRIETARY PRODUCT/MANUFACTURER

1.1 Proprietary Product: Fiberglass-reinforced luxury resilient sheet vinyl. Suitable for Residential environments.

### 1.2 Manufacturer:

Tarkett North America Phone: (800) 899-8916 30000 Aurora Rd. (440) 543-8916 Solon, Ohio 44139

Web: www.tarketthome.com

# 1.3 **Proprietary Product Description:**

1.3.1 **Construction:** Luxury resilient sheet vinyl made from ortho phthalate free, virgin raw materials.

### 1.3.2 Characteristics:

• Construction: Urethane Topcoat Sealed (Low Gloss)

• Series: 15000, HS4, LA, S4

Nominal Thickness: 0.055" (1.4 mm)
 Wearlayer Thickness: 0.010" (0.25mm)

• Width: 12' (3.6 m) and 6' (1.8 m)

Standard Roll Size: 201 yd² (168.1 m²)
 Weight per Square Yard: 2.22 lbs (1.01 kg)

# 2. PRODUCT DETAILS AND TECHNICAL DATA

2.1 Sheet Material: ASTM F1303 Type 1, Grade 3, Class C

2.2 Fire Performance: ASTM E648 > 0.45 W/cm<sup>2</sup>

2.3 Smoke Density: ASTM E662 <450

2.4 HUD/FHA Minimum Property Standards: Meets Wearlayer Thickness

2.5 FloorScore® Certification SCS-EC10.3-2014 v4.1: SCS-FS-02746

2.6 Asthma and Allergy Certified: ASR-1155-03

## 3. INSTALLATION

See FiberFloor installation instructions found at www.tarketthome.com for complete details.

#### 3.1. Methods:

- Releasable
- Permanent
- Floating Glueless

### 3.2. Adhesive:

Tarkett Q-bond One or Tarkett SwiftGrip

Releasable - Medium Nap Roller Permanent - 1/32" x 1/16" x 1/32" trowel

3.3. Seam Sealer: Tarkett DT-65 (Low Gloss)

## 4. AVAILABILITY AND COST

Available through Tarkett Distributors & Retailers.

## MAINTENANCE

See Residential Maintenance instructions found at www.tarketthome.com for complete details.

# 6. TECHNICAL SERVICES

Visit us on the web at <a href="www.tarketthome.com">www.tarketthome.com</a>
Contact Technical Support at (888) 639 8275, or E-mail <a href="Resilient.TechnicalSupport@tarkett.com">Resilient.TechnicalSupport@tarkett.com</a>

## WARRANTY

7 YEAR LIMITED RESIDENTIAL WARRANTY







Technical Services Department 30000 Aurora Road Solon, Ohio 44139 888-639-8275

Resilient.TechnicalSupport@tarkett.com www.tarketthome.com

