

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1 **Proprietary Product:** Fiberglass-reinforced luxury resilient sheet vinyl. Suitable for Residential environments.

1.2 **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
 30000 Aurora Rd. (440) 543-8916
 Solon, Ohio 44139
 Web: www.tarkett.com

1.3 **Proprietary Product Description:**

1.3.1 **Construction:** Luxury resilient sheet vinyl made from ortho phthalate free, virgin raw materials.

1.3.2 **Characteristics:**

- **Construction:** Urethane Topcoat Sealed (Low Gloss)
- **Series:** 01000, BO, CC, CF, D2, HD1, HD, L3, LB, LFO, MO, & M5
- **Overall Thickness:** 0.080" (2.03 mm)
- **Wearlayer Thickness:** 0.010" (0.25mm)
- **Width:** 12' (3.6 m) and 6' (1.8 m)
- **Standard Roll Size:** 144 yd² (120.4 m²)
- **Weight per Square Yard:** 2.65 lbs (1.20 kg)

2. PRODUCT DETAILS AND TECHNICAL DATA

2.1 **Sheet Material:** ASTM F1303 Type 1, Grade 3, Class C

2.2 **Fire Performance:** ASTM E648 >0.45 W/cm²

2.3 **Smoke Density:** ASTM E662 <450

2.4 **HUD/FHA Minimum Property Standards:** Meets Wearlayer Thickness

2.5 **FloorScore® Certification SCS-EC10.3-2014 v4.1:** SCS-FS-02746

2.6 **Asthma and Allergy Certified:** ASR-1155-03

3. INSTALLATION

See FiberFloor installation instructions found at www.tarkett.com for complete details.

3.1. **Methods:**

- Releasable
- Permanent
- Floating Glueless

3.2. **Adhesive:**

- **Tarkett Q-bond One & Tarkett SwiftGrip**
Releasable - Medium Nap Roller
Permanent - 1/32" x 1/16" x 1/32" trowel

3.3. **Seam Sealer:** Tarkett DT-65 (Low Gloss)

4. AVAILABILITY AND COST

Available through authorized Tarkett Retailers.

5. MAINTENANCE

See Residential Maintenance instructions found at www.tarkett.com for complete details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkett.com

Contact Technical Support at (888) 639 8275, or E-mail Resilient.TechnicalSupport@tarkett.com

7. WARRANTY

- 10 YEAR LIMITED RESIDENTIAL WARRANTY
 Aquaguard® 2 Year "No Questions Asked" Warranty



ORTHO-PHTHALATE FREE

Tarkett North America

Technical Services Department
 30000 Aurora Road
 Solon, Ohio 44139
 888-639-8275

Resilient.TechnicalSupport@tarkett.com

www.tarkett.com

