

ProGen™ Rigid Core Luxury Vinyl Flooring Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1 **Proprietary Product:** Waterproof, floating luxury vinyl flooring. Suitable for Residential, Light Commercial, and 3-Season type environments.

1.2 **Manufacturer:**
 Tarkett North America Phone: (800) 899-8916
 30000 Aurora Rd. (440) 543-8916
 Solon, Ohio 44139
 Web: www.tarketthome.com

1.3 Proprietary Product Description:

1.3.1 **Construction:** Rigid core, floating luxury vinyl made with a plastic core and attached acoustical backing.

1.3.2 Characteristics:

- **Locking Mechanism:** Angle-Angle
- **Edge Treatment:** Micro Beveled or Painted Bevel
- **Nominal Thickness:** 0.197" (5 mm)
- **Wear Layer:** .020" (0.5 mm)
- **Core Thickness:** 0.157" (4 mm)
- **Acoustical Backing:** 0.039" (1 mm) IXPE

1.3.3 Plank Size & Packaging

Planks Size	Planks / CTN	SQFT / CTN	Weight / CTN	Cartons / Pallet
5"x 48" (127x1220 mm)	16	26.68 (2.48 m ²)	42.01 (19.05 kg)	56
7"x48" (181x1220mm)	12	28.52 (2.65 m ²)	44.01 (19.96 kg)	50
7"x60" (181x1520mm)	10	29.61 (2.75 m ²)	45.00 (20.41kg)	40
9"x60" (228x1520mm)	8	29.82 (2.77 m ²)	48.12 (21.82 kg)	44
9"x72" (228x1830mm)	6	26.91 (2.50 m ²)	43.44 (20.41kg)	52
12"x24" (305x610mm)	14	28.03 (2.60 m ²)	45.00 (20.41 kg)	54

PRODUCT DETAILS AND TECHNICAL DATA

- 2.1 **Rigid Polymeric Core Specifications:** ASTM F3261 Class 1, Type A or B, Grade 1, Backing Class B
- 2.2 **Dimensional Stability:** ASTM F2199: Passes
- 2.3 **Light Stability:** ASTM F1515 $\Delta\Sigma \leq 8$
- 2.4 **Heat Stability:** ASTM F1514 $\Delta\Sigma \leq 8$
- 2.5 **Residual Indentation:** ASTM F1914: Passes
- 2.6 **Stain Resistance:** ASTM F925: Passes
- 2.7 **Slip Resistance:** ASTM D2047: SCOF ≥ 0.5
- 2.8 **Impact Sound:** ASTM E2179: $\Delta IIC \geq 22$
- 2.9 **Impact Insulation Testing:** ASTM E492 (6" Concrete Slab w/ Drop Ceiling): IIC 68
- 2.10 **FloorScore® Certification:** SCS-FS-09863
- 2.11 **Assure Certified™:** SCS-AC-09930

3. INSTALLATION

See ProGen installation instructions found at www.tarketthome.com for complete details.

4. AVAILABILITY AND COST

Available through authorized Tarkett Retailers.

5. MAINTENANCE

See Residential Maintenance instructions found at www.tarketthome.com for complete details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarketthome.com

Contact Technical Support at (888) 639 8275, or E-mail Resilient.TechnicalSupport@tarkett.com

7. WARRANTY

- LIFETIME YEAR LIMITED RESIDENTIAL WARRANTY
- 15 YEAR LIMITED LIGHT COMMERCIAL WARRANTY
- 10 YEAR 3 SEASONS ROOM LIMITED WARRANTY



**ORTHO-PHTHALATE
FREE***
Except recycled materials

Tarkett North America

Technical Services Department
 30000 Aurora Road
 Solon, Ohio 44139
 888-639-8275

Resilient.TechnicalSupport@tarkett.com

www.tarketthome.com

