1. PROPRIETARY PRODUCT/MANUFACTURER

1.1 **Proprietary Product:** Waterproof, floating luxury vinyl flooring. Suitable for Residential, Light Commercial, and 3-Season type environments.

1.2 Manufacturer:

Tarkett North America	Phone:	(800) 899-8916
30000 Aurora Rd.		(440) 543-8916
Solon, Ohio 44139		
Web: www.tarketthome.com		

1.3 **Proprietary Product Description:**

1.3.1 **Construction:** Rigid core, floating luxury vinyl made with phthalate free, virgin raw materials with a plastic core and attached acoustical backing.

1.3.2 Characteristics:

- Locking Mechanism: Angle-Angle
- Edge Treatment: Square
- Nominal Thickness: 0.177" (4.5 mm)
- Wear Layer: .012" (.30 mm)
- Acoustical Backing: 0.039" (1 mm) IXPE

1.3.3 Plank Size & Packaging

Size	7"x48" (181x1220mm)	7"x60" (181x1520mm)
Planks Per Carton	12	10
Sq Ft per Carton	28.52 (2.65 m ²)	29.61 (2.75 m ²)
Weight per Carton	39.47 lbs (17.9kg)	43.4 lbs (19.7kg)
Cartons per Pallet	55	45



Resilient.TechnicalSupport@tarkett.com

Tarkett North America Technical Services Department

www.tarketthome.com

30000 Aurora Road Solon, Ohio 44139 888-639-8275



SCS Global Services



2. PRODUCT DETAILS AND TECHNICAL DATA

- 2.1 **Rigid Polymeric Core Specification:** ASTM F3261 Class 1, Type A, Grade 2, Backing Class B
- 2.2 Dimensional Stability: ASTM F2199: Passes
- 2.3 Flammability:
 - Fire Performance: ASTM E648 ≥ .45 W/cm²: Class 1
 - Smoke Density: ASTM E662 ≤ 450 optical density
- 2.4 Light Stability: ASTM F515 Δ E \leq 8
- 2.5 Heat Stability: ASTM F1514 $\Delta E \le 8$
- 2.6 Residual Indentation: ASTM F1914: Passes
- 2.7 Stain Resistance: ASTM F925: Passes
- 2.8 Slip Resistance: ASTM D2047: SCOF ≥ 0.5
- 2.9 Impact Sound: ASTM E2179: △IIC ≥ 22 dB
- 2.10 Static Load Limit: ASTM F970: Passes
- 2.11 FloorScore® Certification: SCS-EC10.3-2014 v4.0
- 2.12 Assure Certified™: SCS-AC-07773

3. INSTALLATION

See NuGen Click installation instructions found at <u>www.tarketthome.com</u> for complete details.

4. AVAILABILITY AND COST

Available through authorized Tarkett Retailers.

5. MAINTENANCE

See Residential Maintenance instructions found at <u>www.tarketthome.com</u> for complete details.

6. TECHNICAL SERVICES

Visit us on the web at <u>www.tarketthome.com</u> Contact Technical Support at (888) 639 8275, or E-mail <u>Resilient.TechnicalSupport@tarkett.com</u>

7. WARRANTY

- LIFETIME LIMITED RESIDENTIAL WARRANTY
- 10 YEAR LIMITED LIGHT COMMERCIAL WARRANTY

