



## Bravo™ FiberFloor™

## Product Specification

### 1. PROPRIETARY PRODUCT/MANUFACTURER

1.1 **Proprietary Product:** Fiberglass-reinforced luxury resilient sheet vinyl. Suitable for Residential environments.

1.2 **Manufacturer:**

Tarkett North America Phone: (800) 899-8916  
30000 Aurora Rd. (440) 543-8916  
Solon, Ohio 44139  
Web: [www.tarketthome.com](http://www.tarketthome.com)

1.3 **Proprietary Product Description:**

1.3.1 **Construction:** Luxury resilient sheet vinyl made from ortho-phthalate free, virgin raw materials.

1.3.2 **Characteristics:**

- **Construction:** Urethane Topcoat Sealed (Low Gloss)
- **Series:** M3100
- **Overall Thickness:** 0.100" (2.54 mm)
- **Wearlayer Thickness:** 0.010" (0.25mm)
- **Width:** 12' (3.6 m)
- **Standard Roll Size:** 87 yd<sup>2</sup> (72.74 m<sup>2</sup>)
- **Weight per Square Yard:** 3.09 lbs (1.40 kg)

### 2. PRODUCT DETAILS AND TECHNICAL DATA

2.1 **Sheet Material:** ASTM F1303 Type 1, Grade 3, Class C

2.2 **Fire Performance:** ASTM E648 >0.45 W/cm<sup>2</sup>

2.3 **Smoke Density:** ASTM E662 <450

2.4 **HUD/FHA Minimum Property Standards:** Meets Wearlayer Thickness

2.5 **FloorScore® Certification SCS-EC10.3-2014 v4.1:** SCS-FS-02746

2.6 **Asthma and Allergy Certified:** ASR-1155-03

### 3. INSTALLATION

See FiberFloor installation instructions found at [www.tarketthome.com](http://www.tarketthome.com) for complete details.

3.1 **Methods:**

- Releasable
- Permanent
- Floating Glueless

3.2 **Adhesive:**

- **Tarkett Q-bond One or Tarkett SwiftGrip**  
Releasable - Medium Nap Roller  
Permanent - 1/32" x 1/16" x 1/32" trowel

3.3 **Seam Sealer:** Tarkett DT-65 (Low Gloss)

### 4. AVAILABILITY AND COST

Available exclusively through Menards®, a qualified Tarkett Retailer.

### 5. MAINTENANCE

See Residential Maintenance instructions found at [www.tarketthome.com](http://www.tarketthome.com) for complete details.


### 6. TECHNICAL SERVICES

Visit us on the web at [www.tarketthome.com](http://www.tarketthome.com)

Contact Technical Support at (888) 639 8275, or E-mail [Resilient.TechnicalSupport@tarkett.com](mailto:Resilient.TechnicalSupport@tarkett.com)

### 7. WARRANTY

- 20 YEAR LIMITED RESIDENTIAL WARRANTY



**ORTHO-PHTHALATE  
FREE**

#### Tarkett North America

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
888-639-8275

[Resilient.TechnicalSupport@tarkett.com](mailto:Resilient.TechnicalSupport@tarkett.com)

[www.tarketthome.com](http://www.tarketthome.com)