

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1 **Proprietary Product:** Fiberglass-reinforced luxury resilient sheet vinyl with a polyester backing. Suitable for Residential environments.

1.2 **Manufacturer:**
 Tarkett North America Phone: (800) 899-8916
 30000 Aurora Rd. (440) 543-8916
 Solon, Ohio 44139
 Web: www.tarkett.com

1.3 **Proprietary Product Description:**

1.3.1 **Construction:** Luxury resilient sheet vinyl backed with polyester made from ortho phthalate free, virgin raw materials.

1.3.2 **Characteristics:**

- **Construction:** Urethane Topcoat Sealed (Low Gloss)
- **Series:** 21000
- **Nominal Thickness:** 0.060" (1.55 mm)
- **Wearlayer Thickness:** 0.010" (0.25 mm)
- **Width:** 12' (3.6 m)
- **Standard Roll Size:** 179 yd² (149.7 m²)
- **Weight per Square Yard:** 2.22 lbs (1.21 kg)

2. PRODUCT DETAILS AND TECHNICAL DATA

- 2.1 **Fire Performance:** ASTM E648 >0.45 W/cm²
- 2.2 **Smoke Density:** ASTM E662 <450
- 2.3 **HUD/FHA Minimum Property Standards:** Meets Wearlayer Thickness
- 2.4 **FloorScore® Certification SCS-EC10.3-2014 v4.1:** SCS-FS-02746
- 2.5 **Asthma and Allergy Certified:** AAFC 1541/18/05/01/2066

3. INSTALLATION

See TruTEX & TritonTuff installation instructions found at www.tarkett.com for complete details.

3.1. **Methods:**

- Permanent
- Floating Glueless

3.2. **Adhesive:**

- **Tarkett Q-bond One & Tarkett SwiftGrip**
 Permanent - 1/32" x 1/16" x 1/32" trowel

3.3. **Seam Sealer:** Tarkett DT-65 (Low Gloss)

4. AVAILABILITY AND COST

Available through authorized Tarkett Retailers.

5. MAINTENANCE


See Residential Maintenance instructions found at www.tarkett.com for complete details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkett.com
 Contact Technical Support at (888) 639 8275, or E-mail Resilient.TechnicalSupport@tarkett.com

7. WARRANTY

- 15 YEAR LIMITED RESIDENTIAL WARRANTY



Tarkett North America
 Technical Services Department
 30000 Aurora Road
 Solon, Ohio 44139
 888-639-8275
Resilient.TechnicalSupport@tarkett.com
www.tarkett.com

