



Malibu™ Laminate Flooring

Product Specifications

1. PRODUCT DETAILS

- **Thickness:** 3/8" (9.2mm) with Soundblocker Backer
- **Length:** 47-5/8" (1.2 m)
- **Width:**
 - a. **Heritage Oak Pewter & Woodbridge Oak Charcoal:** 8-1/32" (204 mm)
 - b. **Merrimack Oak Harvest & Coco Berry:** 8-1/16" (205 mm)
- **Edge Type:** Beveled
- **Abrasion Class Rating:** AC3
- **Impact Class Rating:** IC3
- **Includes Attached Pad:** Yes
- **Planks Per Carton:** 7
- **Square Feet Per Carton:**
 - a. **Heritage Oak Pewter & Woodbridge Oak Charcoal:** 18.6 (1.73m²)
 - b. **Merrimack Oak Harvest & Coco Berry:** 18.73 (1.74 m²)
- **Carton Weight:** 23.14 lbs. (10.5 kg).
- **Cartons Per Pallet:** 24
- **FloorScore® Certification SCS-EC10.3-2014 V4.0:** SCS-FS-02386
- Made in the USA with US and Global Parts

2. INSTALLATION - See package insert for complete Installation Information.

Use: Residential

Installation System: T-Lock, Angle-Tap

Location: Below, on and above grade concrete, approved underlayment grade plywood and approved existing floors.

- Tarkett laminate flooring shall acclimate to the temperature of the room. Place unopened cartons of laminate lying horizontally in the room in which they will be installed for a minimum of 48 hours before installation.
- Room temperature shall be a minimum of 65°F (18°C). Relative humidity shall be between 40% and 70%.
- Substrate shall be level to within 1/8" in 8 feet (3.18 mm in 2.4 m).
- Install a 10mil polyethylene vapor retarder when installing over concrete.
- A minimum 5/16" space is required between flooring and all verticals (walls, cabinets, pipes, etc.).
- Rooms over 30' (12m) in length or width will require the use of Tarkett T-Molding.
- The long side of each plank is assembled by inserting the long side tongue into the groove side of the previous row at approximately a 30° angle. Gently slide or position the plank so it is approximately 1/4" away from the short side of the previous plank. Rotate plank downward until lying flat.
- Position tapping block squarely along the groove side end joint and gently tap the block to engage the tongue side of the plank into the groove side of the previous plank. To avoid damaging the planks, make sure to tap in the center of the tapping block.
- The first and last plank in each row shall be at least 12" (30.4 cm) in length. Stagger end joints a minimum of 12" (30.4 cm).

3. WARRANTY - See package insert for complete Warranty Information.

- 30 YEAR LIMITED RESIDENTIAL WARRANTY

4. CARE AND MAINTENANCE

- Post installation temperature must be maintained between 65°F and 85°F. Relative humidity must be maintained between 40% and 70%.
- Never slide heavy furniture or appliances across the floor. Place plywood on the floor and move the object across the plywood.
- To minimize scratching, equip tables and chairs with proper floor protectors.
- To help prolong the life of the floor, use walk-off mats at outside entrances to collect dirt and debris and excess moisture.
- Sweep or vacuum to remove loose dirt or debris that can scratch the floor.
- Wipe up all spills promptly with a dry cloth.
- When necessary, **lightly damp mop** floor with Tarkett SureShine Floor Cleaner or equal neutral floor cleaner. Do not use excessive water when cleaning.



Made in USA with US and Global Parts

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
888-639-8275 Fax 440-498-0025
northamerican.technicalsupport@tarkett.com
www.tarkett.com