

Tarkett FiberFloor® - Moxie™



24001 | Norway Modular 38.5" Drop, DNR



24011 | Wendel Oak Gunstock 18" Drop, DNR



24012 | Wendel Oak 18" Drop, DNR



24101 | Travertine 48" x 72", DNR





24111 | Mix 36" x 36" 18" Drop, DNR



24121 | Colorado Stone 36" x 36". 18" Drop, DNR



24131 | Pompeii 36" x 48" 12" Drop, DNR



24141 | Remix 48" x 72". DNR

According to a recent survey*, respondents identified the following conditions as having the most impact on their household:



66% 49% pollen allergy asthma







of respondents said they are more likely to buy a product if it has an independent third-party certification from a nonprofit organization like AAFA.



What is asthma & allergy friendly certification?

The asthma & allergy friendly certification is a regulated, physician-led certification that accounts for the total installation (product and adhesive) and the ability of a product to be cleaned to minimize the number of allergens released into the environment. This certification helps to set a new standard, and offers consumers a guide for selecting flooring products based on their likelihood to create an allergic or asthmatic reaction.

The top benefits of using CERTIFIED asthma & allergy friendly products

63%

said the products/services reduce their, or their family's exposure to allergy triggers.

reported that the products/services improve air quality in their home.

47%

believe the products/services are better for their health.

Specifications	
Series	24XXX
Nominal Total Thickness	0.125" (3.2 mm)
Wear Layer Thickness	0.012" (0.31 mm)
Wear Layer Finish	Urethane (Low Gloss)
Width	12' (3.6m)
Maximum Roll Size	104 sq. yd. (86.9 m²)
Weight per Sq. Yd.	3.82 lbs (1.7 kg)
ASTM F1303	Type I, Grade 3, Class C
ASTM D2047 (Slip)	>.5
ASTM E648 (Fire)	>.45 W/cm ²
ASTM E662 (Smoke)	<450
ASTM F137 (Flexibility)	1/4" (6,4mm)
ASTM F925 (Staining)	Excellent
ASTM F970 Static Load Limit	75 lbs./sq. in. (5.3 kg/cm²)
ASTM F1514 (Heat Stability)	ΔΕ<8
ASTM F1515 (Light Stability)	ΔΕ<8
ASTM E2179 (Impact Sound Reductions)	Δ IIC 25 dB
Installation System	Glueless or full-spread (Multi-Family Applications)
Location	Below, on and above grade concrete, above grade plywood
Adhesive	Tarkett® QBond-One" or 959
Seam Sealer	Tarkett DT-65 Seam Sealer
HUD/FHA Minimum/HUD	Yes, =/>0.010" wear layer
FloorScore® Certification	SCS-EC10.3-2014: SCS-FS-02746
Ortho-Phthalate Free	Yes
CERTIFIED asthma & allergy friendly * by the Asthma and Allergy Foundation of America (AAFA) & Asthma Society of Canada	AAFC: 1155/11/05/01/2066

^{*} METHODOLOGY: AAFA and Research Now conducted an online survey of adults at least 18 years of age who are a current U.S. resident (n=1844) from August 23 and September 12, 2018 to better understand patient and consumer awareness, perceptions and values of certified products and the asthma & allergy friendly® Certification Program, as well as buyer behaviors and demands.

TOTAL sample size (n=1844) • Public Survey (representative sample) 1005; AAFA Survey (AAFA constituents) 839

The CERTIFIED ASTHMA & ALLERGY FRIENDLY Mark is a Registered Certification Mark of the ASTHMA AND ALLERGY FOUNDATION OF AMERICA and ALLERGY STANDARDS LTD.



Visit tarketthome.com warranty details

Tarkett North America

30000 Aurora Road | Solon, OH 44139 USA: 1-877-TARKETT (1-877-827-5388) Canada: 1-877-436-6267

www.tarketthome.com













Scan this code to visit

www.tarketthome.com